




Commercial Solution Series

CST-2120

*Public Address System
Transformer Module
Quick Start Guide*

公共广播系统音频变压器 快速使用指南



Introduction

The amplifier JBL® part number CST-2120 is a 2-channel stereo amplifier designed to drive two 70V or 100V distributed audio systems.

The amplifier CSA-2120 is a 2-channel stereo amplifier designed to drive two 70V or 100V distributed audio systems.

- The amplifier is designed to drive two 70V or 100V distributed audio systems.
- The amplifier is designed to drive two 70V or 100V distributed audio systems.
- The amplifier is designed to drive two 70V or 100V distributed audio systems.
- The amplifier is designed to drive two 70V or 100V distributed audio systems.

Installation

CAUTION: Before you begin, make sure that the amplifier is disconnected from the power source and all level controls are turned completely down (counter-clockwise).

1. If the amplifier is to be installed in a rack, use a 19-inch (48.3-cm) wide rack (EIA RS-310B) with a minimum depth of 4.5 inches (11.4 cm):
 - Rack depth should be at least 4.5 inches (11.4 cm) for the CSA-2120 amplifier. (See Figure A)
 - Rack width should be at least 19 inches (48.3 cm). (See Figure B)
 - Wall mounting is not recommended. (See Figure C)
2. Connect the amplifier to the distributed audio system using 4-conductor cable.
3. Disconnect the amplifier from the power source before installation.

Note: The CST-2120 amplifier is designed to drive two channels of a 70V or 100V distributed audio system. The amplifier is not designed to drive a single channel of a 70V or 100V distributed audio system. If you are installing the amplifier in a rack, use a rack with a minimum depth of 4.5 inches (11.4 cm).

Specification

安装

1. EI A RS-310B 19
 - CSA-2120 A
 - B
 - C
2. 4
3. CSA-2120
CSA-2120

规

RoHS

部品名						